

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

BACKGROUND OF THE INVENTION

The present invention relates to an automotive control apparatus and method, or more in particular an apparatus and a method for controlling the output of a power train including an engine, a transmission and driving wheels in accordance with the intention of the driver and the result of recognition of other vehicle running immediately ahead.

A conventional technique for changing the drive mode of an automotive vehicle in accordance with the conditions of other vehicle running immediately ahead or the intention of the driver of vehicle is described in Japanese Patent Application Laid-open No. JP-A-47862. This patent publication discloses a method of switching the drive mode of a vehicle in accordance with the driving condition of other vehicle running immediately ahead or in accordance with the intention of the driver of the concerned vehicle, as selectively judged by the driver of the following vehicle. In other words, the driver of the own vehicle determines one of the two drive modes by his or her own judgment so that the driver can drive his or her vehicle with the driving force as intended.

Establishment of a technique for detecting the distance between and relative speeds of one vehicle and

another vehicle running immediately ahead (including an obstacle lying ahead) by use of a radar for securing the safety of the following vehicle is an urgent current problem. In the prior art described above, it is
5 indispensable to attain the drive mode intended by the driver (the linear feeling of acceleration corresponding to the accelerator pedal stroke) and to secure the safety (collision prevention) at the same time.

In the conventional method of controlling the
10 drive mode of a vehicle which still finds applications, however, primary emphasis is always placed on the intention of the driver. Therefore, it is technically difficult to automatically switch the drive mode of a following vehicle taking both the safety of the
15 particular following vehicle and the driving condition of a vehicle running immediately ahead into consideration. This switching operation has hitherto been left to the manipulation of the driver of the following vehicle. As a result, if the difference is large
20 between the calculated control parameter values of the above-mentioned two drive modes, the torque changes so abruptly that an unexpected acceleration/deceleration change occurs unavoidably against the will of the driver of his own vehicle.

25 In the prior art, assume, for example, that the driver who has so far maintained the accelerator pedal stroke at a low value switches to a mode

corresponding to the driving condition of a vehicle running immediately ahead, i.e. a mode for chasing the vehicle running immediately ahead. A deviation occurs between a target value intended for by the driver of the vehicle and an actual target control value for the chasing operation, thereby causing an undesirable torque change uncomfortable to the driver of the vehicle.

JP-A-7-189795 and JP-A-8-304548 disclose that an engine and a transmission are controlled with the control parameter such as a driving torque at a output shaft of the transmission.

SUMMARY OF THE INVENTION

The object of the present invention is to provide an automotive control apparatus and control method, in which a control amount for securing the safety of a vehicle and a control amount for attaining a mode intended for by the driver of the vehicle can be switched while reducing the shock from the power train, thus making it possible to secure the safety and the maneuverability of the vehicle at the same time.

The present invention provides an automotive control apparatus, in which fluctuations of at least selected one of the driving torque, the driving force and the acceleration/deceleration rate are suppressed in the case where a deviation beyond a predetermined value occurs between a first target value before change of at

least one of the driving torque, the driving force and the acceleration/deceleration rate and a second target value calculated in accordance with the drive mode intended for by the driver or the driving environment ahead.

According to a first preferred aspect of the invention, there is provided an automotive control apparatus for setting a target value of the driving torque on the output shaft side of the transmission based on at least the accelerator pedal stroke and controlling at least the engine torque in accordance with the target value, comprising means for setting a drive mode intended for by the driver or means for recognizing the driving environment ahead, means for changing a target value in accordance with the signal produced from one of the foregoing two means, and means for suppressing the fluctuations of the driving torque in the case where a deviation of not less than a predetermined value occurs, in switching the target values, between the first target value before change and the second target value calculated according to the above-mentioned signal.

According to a second preferred aspect of the invention, there is provided an automotive control apparatus comprising means for detecting an actual vehicle acceleration/deceleration rate and means for detecting an actual vehicle speed in addition to the accelerator pedal stroke as a signal used for

calculating a target value of the driving torque.

According to a third preferred aspect of the invention, there is provided an automotive control apparatus in which the torque fluctuation suppression
5 means causes the target value change means to change the first target value first at a predetermined progressive rate for a predetermined length of time from an initial value and switches it to a second target value when the deviation between the first and second target values is
10 reduced to a predetermined level.

According to a third preferred aspect of the invention, there is provided an automotive control apparatus, in which the torque fluctuation suppression means causes the target value change means to switch the
15 second target value to the first target value instantaneously.

According to a fourth preferred aspect of the invention, there is provided an automotive control apparatus, in which the signal produced by the drive
20 mode setting means or the environment recognition means represents the headway distance and the relative speed with the vehicle running immediately ahead.

According to a fifth preferred aspect of the invention, there is provided an automotive control
25 apparatus for setting a target value of the driving torque on the output shaft side of the transmission based on at least the accelerator pedal stroke and the actual vehicle deceleration rate and controlling at

least the engine torque and the transmission ratio in accordance with the target value, comprising means for calculating a target value of the rotational speed on the input shaft side of the transmission in accordance with the target value and a target rotational speed limit setting means for setting a limit to the target rotational speed on the input shaft side of the transmission.

According to a sixth preferred aspect of the invention, there is provided an automotive control apparatus for setting a target value of the driving torque on the output shaft side of the transmission based on at least the accelerator pedal stroke and the actual vehicle deceleration rate and controlling at least the engine torque and the transmission ratio in accordance with the target value, comprising means for calculating a target value of the transmission ratio in accordance with the target value of the driving torque and target transmission ratio limit setting means for setting a limit to the transmission ratio.

According to a seventh preferred aspect of the invention, there is provided an automotive control apparatus for setting at least one of the driving torque, the driving force and the acceleration/deceleration rate on the output shaft side of the transmission as a target value based on at least the accelerator pedal stroke and controlling at least the engine torque in accordance with the target value, comprising means

for calculating the driving load of the vehicle, means
for calculating the actual deceleration rate of the
vehicle, means for calculating a target deceleration
rate based on at least the deceleration rate calculated
5 y the deceleration rate calculation means and the
accelerator pedal stroke, and means for calculating the
target value in accordance with the driving load calcu-
lated by the driving load calculation means and the
target deceleration rate calculated by the target
10 deceleration rate calculation means.

According to an eighth aspect of the inven-
tion, there is provided an automotive control apparatus
wherein the driving load calculation means is weight
rewrite means capable of rewriting the magnitude of the
15 driving load calculated.

These means can solve the above-mentioned
problems.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing the process
20 of control according to an embodiment of the present
invention.

Fig. 2 is a diagram showing a system
configuration according to the invention.

Fig. 3 is a time chart for changing a first
25 target value to a second target value.

Fig. 4 is a time chart for changing a second
target value to a first target value.

Fig. 5 is a block diagram showing the process of control according to another embodiment of the invention.

Fig. 6 is a time chart for controlling a target deceleration rate.

Fig. 7 is a time chart for switching between deceleration and acceleration.

Fig. 8 is a characteristic diagram schematically showing the transmission ratio control for deceleration.

Fig. 9 is a perspective view showing a shift lever 40 for briefly explaining a method of manually setting a critical engine speed.

Fig. 10 is a time chart for target deceleration rate control using an actual deceleration rate G_d .

Fig. 11 is a time chart for controlling the throttle valve opening during change shift operation.

Fig. 12 is a time chart showing a deceleration rate characteristic for different road slopes.

Fig. 13 is a block diagram for calculating a target value corresponding to the driving load.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

An embodiment of the invention will be described below with reference to the accompanying drawings.

Fig. 1 is a block diagram showing the control operation according to an embodiment of the invention.

First, a control logic will be explained for the case in which an ordinary driver operates the accelerator pedal (not shown) to drive a vehicle (not shown).

The vehicle control system includes an
5 environment based power train control unit 23, an engine power train control unit 19 and various sensors and detectors for detecting an accelerator pedal stroke, a vehicle speed, an engine speed, transmission input/output speeds, a headway distance, a relative speed, a
10 steering angle, a throttle opening, a brake depression force and states of some switches. The environment based power train control unit 23 and the engine power train control unit 19 are formed by a microcomputer including MPU and memory devices (not shown). The MPU
15 executes the control programs stored in the memory devices. Every function of every unit included in the environment based power train control unit 23 and the engine power train control unit 19 is implemented in accordance with the control programs.

20 The accelerator pedal depression stroke α and the vehicle speed N_0 are applied to a first target driving torque calculation unit 1, where a first target value $Ttar1$ is calculated and applied to a target value change unit 2. The first target value $Ttar1$ from the
25 target value change unit 2 is directly substituted into the target value $Ttar$, so that the target value $Ttar$ is applied directly to a target brake force calculation unit 3, a target engine torque calculation unit 4 and a

target transmission ratio calculation unit 5.

The calculation unit 3 retrieves a brake control range composed of the target value T_{tar} and the target rotational speed on the transmission input shaft side thereby to calculate a target brake force B_t . This
5 target brake force B_t is applied to a brake actuator 6 thereby to execute the brake control.

The target transmission ratio calculation unit 5 calculates a target transmission ratio I_t with the
10 target value T_{tar} and the vehicle speed N_0 as parameters during acceleration. During deceleration, on the other hand, the engine brake control area composed of the target value T_{tar} and the target rotational speed on the transmission input shaft side shown in Fig. 8 is
15 retrieved thereby to calculate the target transmission ratio I_t . This target transmission ratio I_t is applied to a transmission actuator 7 thereby to execute the acceleration control and the engine brake control.

Further, the target engine torque calculation
20 unit 4 calculates a target engine torque T_{et} from the target value T_{tar} and the target transmission ratio I_t , which target engine torque T_{et} is applied to a target throttle valve opening calculation unit 8. A target throttle valve opening θ_t is calculated and applied to a
25 throttle actuator 9. In the process, an actual transmission ratio I_r providing the ratio between the input shaft rotational speed N_t of the transmission and the vehicle speed N_0 can be used in place of the target

transmission ratio I_t , so that the ability of the actual driving torque to follow the target torque T_{tar} is improved for an improved torque control.

A similar effect is obtained by using the
5 longitudinal vehicle acceleration or the driving force in place of the driving torque. Further, instead of the brake control used in the present embodiment, the engine torque and the transmission ratio can be controlled to control the acceleration/deceleration rate in a way
10 superior to the prior art, thereby making it possible to drive the vehicle as intended by the driver.

The foregoing description concerns an automotive vehicle carrying an engine in which fuel is injected into an air inlet port. In another type of
15 engine in which fuel is injected directly into a combustion cylinder, since larger air-fuel ratio mixture can be used by employing a combination of the throttle valve control and the fuel amount control for controlling the air-fuel ratio, therefore, a driving torque
20 control of higher accuracy is made possible.

Now, an explanation will be given of a control logic for the case in which a constant vehicle speed control or a constant headway distance control is requested as a drive mode by the driver instead of
25 normal drive through a drive mode changeover switch SW or the like. The term "headway distance" means a distance between a car and the one in front.

In Fig. 1, assume that a constant vehicle

speed control is requested. A target vehicle speed V_t and a vehicle speed N_0 are applied to a second target driving torque calculation unit 10, in which a target acceleration/deceleration rate is determined from the deviation between the target vehicle speed V_t and the vehicle speed N_0 and the time required for reaching the target vehicle speed V_t . Further, a second target value $Ttar2$ is calculated using the vehicle weight, the tire radius, the gravity and the driving resistance on flat roads of ordinary altitude. The second target value $Ttar2$ is applied to a limit setting unit 11. The second target value $Ttar2$, if it exceeds a target critical driving torque $Ttar2'$, as shown in Fig. 4, is limited to the critical driving torque $Ttar2'$. As a result, an abrupt acceleration can be avoided while the vehicle is running at a constant speed. Thus, the acceleration control is possible which gives no uncomfortable feeling to the driver. Then the actuators 6, 7, 9 are driven to drive the vehicle with the critical driving torque $Ttar2'$ or the second target value $Ttar2$ as a target value in place of the first target value $Ttar1$ for normal drive.

The target value is changed this way by the signal of the changeover switch SW. The control logic executed by the driver through the changeover switch SW incorporates a logic for changing the target value automatically in the case where the headway distance St is judged to have dangerously decreased to a considerably

small value. Specifically, the driving environment in front is recognized by a radar or a camera and the result of recognition is applied to the target value change unit 2, so that the target driving torque is
5 automatically changed from the first target value $Ttar1$ to the second target value $Ttar2$.

In the case where a constant headway distance control is requested, on the other hand, the speed Vs of a following vehicle relative to the speed of the vehicle
10 running immediately ahead, the headway distance St with the vehicle running immediately ahead, the target headway distance Stt with the vehicle running immediately ahead and the vehicle speed N_0 of the following vehicle are applied to the second target driving torque calcu-
15 lation unit 1. A target acceleration/deceleration rate is determined from the difference between the vehicle speed N_0 and the target vehicle speed Vtt determined from the relative speed Vs , the headway distance St and the target headway distance Stt relative to the vehicle
20 running immediately ahead on the one hand and the time required for reaching a target vehicle speed on the other hand. Further, the second target value $Ttar2$ is calculated using the vehicle weight, the tire radius, the gravity and the driving resistance on flat roads of
25 ordinary altitude. After that, the control operation similar to that for the above-mentioned constant vehicle speed control is performed.

A method of changing between the first target

value Ttar1 and the second target value Ttar2 will be explained with reference to Figs. 3 and 4.

Fig. 3 is a time chart for changing from the first to the second target value, and Fig. 4 is a time
5 chart for changing from the second to the first target value. In Fig. 3, consider the case in which α is larger than zero, i.e. the case in which the target value of the driving torque is changed from the first to the second value at a timing a while the vehicle is
10 accelerating. At timing a, the second target value Ttar2 is calculated and the target is changed from the first target value Ttar1 to the second target value Ttar2. If the target vehicle speed V_t or the target vehicle speed V_{tt} is considerably higher than the
15 current vehicle speed N_0 , the deviation Δk between the first target value Ttar1 and the second target value Ttar2 assumes a large value. Consequently, once the target value is changed directly at timing a, the actual wheel torque undergoes a change (as in the prior art) to
20 cause uncomfortable to ride.

According to the present invention, in contrast, when the target is changed from the first target value Ttar1 to the second target value Ttar2 at timing a, the target value Ttar is steadily increased
25 before a timing b after the lapse of a predetermined time length T_s within the target change means 2, and the second target value Ttar2 is not used before the second target value Ttar2 and the target value Ttar reaches a

predetermined value k_1 free of torque change. As a result, the fluctuations in the actual wheel torque generated after timing a can be suppressed, thereby making possible a smooth change in target value, i.e. a
5 consistent transfer to a constant vehicle speed control and a constant headway distance control.

Now, in Fig. 4, consider the case in which the target driving torque is changed from the second target value T_{tar2} to the first target value T_{tar1} at timing c
10 while the accelerator pedal stroke α is larger than zero, i.e. while the vehicle is accelerating. At timing c , the first target value T_{tar1} is calculated from the accelerator pedal stroke α and the vehicle speed N_0 , and the target is changed from the second target value T_{tar2}
15 to the first target value T_{tar1} . In this case, the intention of the driver to accelerate is given priority, and therefore the target value is changed instantaneously. Also, a time constant of about 200 seconds or less can be set at which the feeling of acceleration is
20 not deteriorated.

Fig. 2 is a diagram showing a system configuration of the invention. A vehicle body 15 has mounted thereon an engine 16 and a transmission 17. The driving force transmitted in the power train including the
25 engine 16 and wheels 18 is controlled by an engine power train control unit 19. This engine power train control unit 19 calculates the first target value T_{tar1} of the driving torque (or the driving force or the acceleration

rate), and, in accordance with the target value thus
calculated, further calculates a target throttle valve
opening θ_t (or a target air flow rate), a fuel amount,
an ignition timing, a brake pressure B_t , a transmission
5 ratio I_t and a transmission control oil pressure P_L .
The fuel amount is controlled by an inlet port injection
method which is currently used most widely or a direct
injection method high in controllability.

The vehicle body 15 also carries a TV camera
10 20 for detecting the environmental conditions and an
antenna 21 for receiving the information on the
infrastructure. The image on the TV camera 20 is
applied to and processed in an image processing unit
22 to recognize a road slope, the radius of curvature
15 of a corner, traffic signal information, road marks,
traffic control situation, other vehicles, pedestrians,
obstacles, etc. A driving environment signal produced
by this recognition is applied to an environment-based
power train control unit 23.

20 Also, a radar system 24 of FM-CW type or the
like is installed on the front part of the vehicle 15 to
detect the distance S_t from or the relative speed V_s
with a vehicle running immediately ahead or an object
lying ahead. The antenna 21 is connected with an
25 infrastructure information terminal 25 for supplying the
infrastructure information by which to detect the
conditions of the roads ahead (wet or dry, depth of
water pools, snow condition, frozen or not, presence or

absence of gravel, etc.), weather information (rainfall, snowfall, etc.), traffic congestion, etc. Further, from the road surface condition, the friction coefficient μ between the tire and the road is calculated and applied
5 to the control unit 23.

The driving environment can also be judged from the map information stored in a CD-ROM 26 or the like, so that the road conditions ahead (slope, corner radius of curvature, traffic control, etc.) can be
10 detected.

In the control unit 23, the second target value $Ttar2$ of the driving torque of the power train (or the driving force or acceleration rate) corresponding to the driving environment to be overcome is calculated on
15 the basis of the signals representing the road slope, the corner radius of curvature, the headway distance St , the relative speed Vs , the friction coefficient μ , etc. The calculation result is applied to the control unit 19.

20 The control unit 19 selects the first target value $Ttar1$ or the second target value $Ttar2$ according to the signal of the changeover switch SW manipulated by the driver. Assume that the second target value $Ttar2$ is selected. Based on this value, i.e. based on the
25 target driving torque corresponding to the driving environment, the throttle valve opening θ_t , the fuel amount, the ignition timing, transmission control oil pressure PL , the transmission ratio It and the brake

force B_t are calculated. Also, the control unit 19 is supplied with an accelerator pedal stroke α , a vehicle speed N_0 , an engine speed N_e , a switch signal M_{sw} (described later), an acceleration sensor signal G_d , a steering wheel angle S_a , etc.

Fig. 5 is a block diagram showing the control operation according to another embodiment. The power train controller providing the base of this operation is identical to that shown in Fig. 1. The difference of this embodiment from the above-mentioned embodiment lies in the engine brake control. In Fig. 1, the engine brake is controlled by controlling the transmission ratio, while the embodiment of Fig. 5 newly includes an engine brake control unit 30 and an engine brake actuator 31. Specifically, a one-way clutch of the stepped transmission and a clutch for turning on/off the operation of the one-way clutch are used to judge whether the inverse driving force from the tires running on a descendant slope is to be transmitted or not to the engine. This system can realize a smooth deceleration control.

Fig. 6 is a time chart for the case in which the target deceleration rate is controlled as described in Fig. 5. First, a target driving torque T_{tar} of negative value is calculated by a combination of the accelerator pedal stroke α and the vehicle speed N_0 or a combination of the accelerator pedal stroke α , the vehicle speed N_0 and the actual vehicle deceleration

rate G_d (described in detail with reference to Fig. 10).
As an alternative, the target value T_{tar} of the driving
torque is set by the second target value T_{tar2} of the
driving torque supplied from the environment-based power
5 train control unit 23. In a large deceleration control
requiring the brake control in accordance with this
target value T_{tar} (period between e and f), the target
engine torque T_{et} is set to almost zero, i.e. the
vicinity of a minimum value, and further, the target
10 transmission I_t is set in accordance with the value of
the target engine torque T_{et} to achieve the target
driving torque value T_{tar} . During the period between e
and f, however, it is necessary to turn off the engine
brake control signal E_b in order to avoid the feeling of
15 deceleration which otherwise might be caused by the
interference between the brake control and the engine
brake control by the transmission ratio control. As a
result, the deceleration is controlled only by the brake
control, and therefore the controllability and the
20 maneuverability for deceleration are improved.

Further, since the transmission ratio is
shifted to the lower side (associated with a larger
transmission ratio) at the time of deceleration, the
feeling of acceleration is improved when actuating the
25 accelerator pedal again.

Now, a method of switching from deceleration
to acceleration will be explained taking the cornering
control as an example with reference to Fig. 7. Fig 7

is a time chart for the deceleration-acceleration switching control.

An acceleration/deceleration rate change judging means 32 of Fig. 5 judges whether the state in which the accelerator pedal stroke α is zero and the target value T_{tar} of the driving torque and the target engine torque T_{et} are negative has changed to the state in which the accelerator pedal stroke α , i.e. the target value T_{tar} of the driving torque is positive. Assume that the target value T_{tar} of the driving torque has turned positive and an acceleration is judged. A transmission ratio change limiter 33 holds the current transmission ratio or limits the margin of change in the transmission ratio. In view of the fact that the transmission ratio is shifted to low side (associated with a larger transmission ratio) during the deceleration, the engine speed increases at a faster rate during the acceleration (not shown), thereby improving the feeling of acceleration.

In Fig. 7, the period T_{l1} during which the current transmission ratio is held or the margin of change in transmission ratio is limited is determined by the magnitude of the target value T_{tar} of the driving torque, etc. A large target value T_{tar} of the driving torque indicates that a large acceleration rate is required. In such a case, therefore, it is necessary to increase the holding or limiting period, as the case may be. In the case where the steering angle S_a undergoes a

change during the period T11, i.e. in the case where a cornering is judged, the holding or limiting period is extended to a time point (after the lapse of period T12) when the steering angle Sa returns to zero (i.e.

5 straight run). In the case where the cornering continues, the period can be extended to T13. Detection and judgment as to a cornering or not can be made alternatively based on the road radius of curvature R determined from the steering angle Sa (calculated by a
10 road curvature radius estimation unit 34), a lateral acceleration sensor, a yaw rate sensor, infrastructure information, navigation information, etc. In this connection, the limited margin in the change of transmission ratio is set within ± 0.5 or less so as not to
15 adversely affect the feeling of acceleration according to this embodiment.

Now, an explanation will be given of a method of setting the transmission ratio for controlling the target deceleration rate. For acceleration, the
20 conventional transmission ratio map or a transmission ratio taking the fuel consumption into account can be used. For deceleration, however, the requirement of engine brake makes it not an easy matter to set the transmission ratio. In the prior art, the automatic
25 transmission fails to work as intended by the driver in this operation area of deceleration. According to this invention, the above-mentioned problem is solved using

the method described below with reference to Figs. 5 and 8.

Fig. 8 is a characteristic diagram schematically showing the transmission ratio control for deceleration. In Fig. 8, the abscissa represents the target rotational speed on the transmission input shaft side (associated with the target transmission ratio I_t for a constant vehicle speed N_0), and the ordinate represents the target driving torque value T_{tar} (i.e. the target deceleration rate) of negative value.

The area along the abscissa is for brake control, and the hatched area for the transmission ratio control including the engine brake control. In the continuously variable transmission, the control level can be set arbitrarily any point over the whole hatched area. For the stepped transmission (such as a transmission having four steps of transmission ratio for forward drive), however, only the control value can be set on the solid line in the hatched portion.

First, the continuously variable transmission will be described. Assuming that the target value T_{tar} of the driving torque is set at point A in Fig. 8, for example, any transmission ratio on the solid line between points B and C in the hatched portion can be selected. For determining a target transmission ratio from among numerous transmission ratios, therefore, some conditions must be set. Such conditions can be the purpose of deceleration on the part of the driver,

safety and fuel economy. A target critical engine speed is used as a parameter for meeting these conditions. By setting the target critical engine speed N_{lmt} at a value associated with point D, for example, the engine speed
5 on the target transmission input shaft side at point D, i.e. the target transmission ratio can be determined.

Now, the stepped transmission will be explained. In this case, once the target value T_{tar} of the driving torque is set at point A, only the trans-
10 mission ratio intersecting the point A representing the shift position of the first or second speed is selected among those transmission ratios on the four thin solid lines in the hatched portion. In the case where the target critical engine speed N_{lmt} is set to a value at
15 point D as described above, however, the selection of the second speed associated with a larger value than that the one at point D is impossible, resulting in unavoidable selection of the first speed. Under this condition, however, the deceleration rate is associated
20 with point E and the target deceleration rate cannot be achieved. Therefore, the engine torque is increased to set the target critical engine speed N_{lmt} to point D. The engine torque is increased by increasing the
throttle valve opening or by increasing the fuel amount.

25 As described above, a negative transmission ratio is set based on the target value T_{tar} of the driving torque and the critical engine speed N_{lmt} , so that it is possible to solve the problem of the prior

art that the automatic transmission fails to operate as intended by the driver in the deceleration range of operation. The target critical engine speed N_{lmt} is set in the transmission ratio limiter 35 based on the signal
5 of the manual critical engine speed setting switch Msw shown in Fig. 5, and applied to the target transmission ratio calculation unit 5. The target transmission ratio calculation unit 5 calculates and outputs the target transmission ratio I_t based on the target value T_{tar} of
10 the driving torque, the target critical engine speed N_{lmt} and the characteristic of Fig. 8 stored in a memory (not shown) or the like.

Fig. 9 is a perspective view of a shift lever
40 for briefly explaining a method of setting the manual
15 critical engine speed by the manual critical engine speed setting switch Msw of Fig. 8.

The operation of the shift lever 40 can select an economy mode (EM), a normal drive mode (NDM) and a sport mode (SM). In NDM, the critical engine speed for
20 engine brake is set at a predetermined value as low as about 1500 rpm to prevent a high deceleration rate. In ED, the fuel consumption is a more important factor than the engine speed, and therefore a transmission ratio is set taking the fuel consumption into consideration. For
25 deceleration, the engine brake range is widened as far as possible while satisfying a target deceleration rate, and fuel supply is suspended to reduce the fuel consumption. In SM, on the other hand, the target critical

engine speed Nlmt of Fig. 8 can be set by the operation of the driver. Specifically, the target critical engine speed Nlmt is increased to HIGH position or decreased to LOW position of Fig. 9 by manipulating the shift lever
5 40 several times repeatedly. The resulting magnitude is detected by the manual critical engine speed setting switch Msw. The signal from the manual critical engine speed setting switch Msw is applied to an engine power train control unit 19, and the target critical engine
10 speed Nlmt is set by the transmission ratio limiter 35. Also, the target critical engine speed Nlmt is output to a display unit 41 from the engine power train control unit 19, and thus the driver is informed of the current drive mode in such a form as SPORT MODE, LIMITER REV
15 4000 RPM. When using the second target value Ttar2 of the driving torque, on the other hand, the acceleration/deceleration rate is controlled with stress placed on safety in whichever mode.

Fig. 10 is a time chart for target deceleration control using an actual deceleration rate Gd. The
20 accelerator pedal stroke α is judged to have decreased to zero or lower, a signal representing an actual deceleration rate Gd is detected for an arbitrary length of time (period between g and h), and a target deceleration rate is calculated. Specifically, since the
25 change in the deceleration rate Gd lags behind the change in the accelerator pedal stroke α , it is necessary to set a period of arbitrary length for deciding a

target deceleration rate. In the case where the brake pedal depression force β increases during this decision period, for example, the prevailing deceleration rate G_d is used as a target deceleration rate. As a result, the power train actually starts to be controlled at time point h. The brake depression force β may be represented by a braking pressure, a brake pedal depression stroke or a signal indicative of operation of the brakes.

10 If the above-mentioned decision period is excessively long, however, the intention of the driver and the safety encounter a problem, whereas if the decision period is too short, judgment of the deceleration rate aimed at by the driver is difficult. It is therefore empirically proper to set the decision period at 300 ms to 800 ms.

For the stepped transmission, the target transmission ratio I_t is set from the fourth speed to the third speed when the brake pedal is not actuated and from the fourth speed to the second speed when the brake pedal is actuated, based on the transmission ratio control described with reference to Fig. 8. Also, the target throttle valve opening θ_t is controlled during the speed change in order to improve the speed change response. A detailed explanation will be given below with reference to Fig. 11.

Fig. 11 is a time chart for throttle valve opening control during speed change. Especially for the

stepped transmission, the transmission ratio is required to be changed in large steps, and therefore auxiliary control by the engine torque control applies effectively. Specifically, whether the speed is undergoing a change is determined using the actual transmission ratio I_r , and judgment is made as to whether the transmission ratio I_r has reached a value associated with the time k_2 for starting the throttle control. In the case where the time k_2 has arrived, the engine speed expected to change after speed change operation is predicted, and the throttle valve opening corresponding to the particular engine speed is calculated and output. The oil pressure PL supplied to the clutch of the transmission in the process is reduced beforehand at the time point of generation of a transmission start command signal. This makes possible a rapid shift-down operation. At time point k_3 , the throttle control is terminated for increasing the engine speed, and the process proceeds to the step of decreasing the target deceleration rate described with reference to Fig. 8. At the same time, an oil pressure PL corresponding to the target engine torque T_{et} , i.e. the target throttle opening θ_t is set upward. In this way, the target deceleration control makes shift-down difficult with the decrease in engine speed, and therefore makes indispensable the cooperative control of the throttle valve opening and the oil pressure shown in Fig. 11.

Fig. 12 is a time chart showing the decele-

ration rate characteristic with different road slope inclinations, and Fig. 13 is a block diagram for calculating a target value corresponding to a driving load.

5 In Fig. 12, the solid line represents a deceleration characteristic with the accelerator pedal stroke α of zero on flat roads of normal altitude, the dotted line represents a deceleration characteristic with the accelerator pedal stroke α of zero on a
10 descending slope, and the dashed line represents a deceleration characteristic with the accelerator pedal stroke α of zero on an ascending slope. The difference between solid line and dotted line or dashed line represents a driving load TL. As described above, the
15 target deceleration rate is determined as required by the driver during an arbitrary length of time after the accelerator pedal stroke α is reduced to zero. Assume, for example, that the power train is controlled to achieve the actual deceleration rate when the driver has
20 reduced the accelerator pedal stroke α to zero. This deceleration rate is the target value required by the driver.

On a descending slope, on the other hand, the driving load is reduced, and therefore, the deceleration
25 rate is also reduced, i.e. the operation shifts toward acceleration. As a result, the driver feels uncomfortable and the different deceleration rate from the one required by the driver, and the driver apply the

brakes. On an ascending slope, on the other hand, the driving load is high, and therefore the deceleration rate increases, i.e. the operation shifts towards deceleration. Consequently, the driver feels

5 uncomfortable, and the deceleration different from the one required by the driver, and the driver actuates the accelerator pedal.

In view of this, the driving load is determined as described above, and a target deceleration rate
10 is determined and corrected in accordance with this driving load. In this way, the acceleration control corresponding to the change in the road slope inclination is realized. The driving performance is further improved if the driving load is corrected by the age,
15 sex, etc. of the driver.

Now, the control logic of Fig. 12 will be explained with reference to Fig. 13. First, the vehicle speed N_0 is applied to the deceleration rate calculation means 45 thereby to calculate the actual vehicle deceleration G_d . The deceleration rate G_d , the accelerator
20 pedal stroke α and the brake pedal depression signal β are applied to the target deceleration rate calculation unit 46 thereby to calculate the target deceleration rate G_{dt} .

25 The target deceleration rate G_{dt} is calculated in the case where the accelerator pedal stroke α becomes zero and the brake pedal depression signal β changes during the target deceleration rate determining period

of Fig. 12.

Then, the vehicle speed N_o , the turbine speed N_t and the engine speed N_e are applied to the driving torque calculation unit 47, so that the actual driving torque T_o is calculated. The driving torque calculation unit 47 determines the driving torque T_o from the torque converter characteristic and the transmission ratio undergoing an abrupt change in initial stages of the speed change. The driving torque is calculated in a similar manner to the method described in detail in JP-A-6-207660.

The driving torque T_o , the deceleration rate G_d and the vehicle speed N_o are applied to the driving load calculation unit 48 thereby to calculate the driving load T_L . In Fig. 13, the driving load T_L is expressed by a functional equation. Actually, however, it can be determined from the following equation (1) for vehicle drive.

$$T_L = T_o - I_v \cdot G_d \quad (1)$$

where I_v is the inertial mass of the vehicle.

Finally, the driving load T_L and the target deceleration G_{dt} are applied to the first target driving torque calculation unit 1 thereby to calculate the first target value T_{tar} . This conversion equation is based on equation (1). The first target value T_{tar} can alternatively be determined by experiments from the actual

vehicle characteristics. The calculations including and subsequent to the target engine torque calculation unit 4 are similar to the corresponding calculations in Fig. 1.

5 The weight \underline{b} of the functional equation of the driving load calculation unit 48 of Fig. 13 will be described below.

 Generally, different drivers prefer different deceleration rates on an ascending or descending slope.
10 This deceleration rate can be freely changed according to this invention. A rewrite switch signal that can be manipulated by the driver is applied to a weight rewrite unit 49 and thus the deceleration on an ascending or descending slope can be freely changed. Specifically,
15 the weight \underline{b} calculated in the weight rewrite unit 49 is input to the driving load calculation unit 48, thereby making it possible to change the magnitude of the driving load TL.

 The above-mentioned application of the control
20 logic suppresses the fluctuations of the torque produced from the power train when switching between the control amount for securing the vehicle safety and the control amount for achieving the mode intended for by the driver. At the same time, an acceleration rate or a
25 deceleration rate not intended for by the driver is prevented. In this way, the deceleration rate required by the driver is obtained in all driving environments including flat roads at normal altitude and ascending

and descending slopes. A comfortable ride and a safety compatible with a superior maneuverability can thus be realized.